

In the Claims:

1. (previously presented) An apparatus for determining an unbalance of a rotational body when said rotational body is mounted on said apparatus so as to be rotatable about a rotation axis, said apparatus comprising:

a mounting plate extending along and defining a plate plane;

a mounting fixture that is arranged on said mounting plate, and that is adapted to receive the rotational body mounted thereon so as to allow the rotational body to rotate about said rotation axis, wherein said rotation axis is oriented perpendicular to said plate plane;

an outer frame arranged at least partially outwardly around said mounting plate;

plural pairs of webs on said plate plane, said webs respectively connecting said mounting plate to said outer frame in an arrangement of said webs that is symmetrical relative to said rotation axis, wherein said webs are so configured and arranged so as to support said mounting plate relative to said outer frame, to transmit from said mounting plate to said outer frame all axially directed forces that are oriented along said rotation axis and that are not induced by the unbalance of the rotational body, and to allow said mounting plate to undergo translational vibration relative to said outer frame in said plate plane, wherein said translational vibration is induced in said mounting plate by the unbalance of the rotational body; and

27 a first vibration transducer arrangement that is  
28 coupled to said outer frame and to said mounting plate, and  
29 that is so arranged and adapted to detect said  
30 translational vibration of said mounting plate relative to  
31 said outer frame in said plate plane.

1 2. (original) The apparatus according to claim 1, wherein said  
2 webs are further so configured and arranged so as to define  
3 a pivot axis perpendicular to said rotation axis, and so as  
4 to allow said mounting plate to undergo pivotal vibration  
5 relative to said outer frame about said pivot axis, wherein  
6 said pivotal vibration is induced in said mounting plate by  
7 the unbalance of the rotational body.

1 3. (original) The apparatus according to claim 2, further  
2 comprising a second vibration transducer arrangement that  
3 is coupled to said outer frame and to said mounting plate,  
4 and that is so arranged and adapted to detect said pivotal  
5 vibration of said mounting plate relative to said outer  
6 frame about said pivot axis.

1 4. (original) The apparatus according to claim 3, wherein said  
2 first vibration transducer arrangement has a first  
3 effective measuring axis that is oriented always  
4 perpendicular to said pivot axis and substantially  
5 perpendicular to said rotation axis, and said second  
6 vibration transducer arrangement has a second effective  
7 measuring axis that is oriented substantially perpendicular

3896/WFF:ar

- 3 -

to said plate plane at a location offset from said pivot axis.

5. (original) The apparatus according to claim 3, wherein said first vibration transducer arrangement has a first effective measuring axis that is oriented coincident with said pivot axis, and said second vibration transducer arrangement has a second effective measuring axis that is oriented substantially perpendicular to said plate plane at a location offset from said pivot axis.

6. (original) The apparatus according to claim 3, wherein said mounting plate comprises a plate body on which said mounting fixture is arranged and an extension arm protruding outwardly from said plate body, said outer frame comprises a plurality of frame members arranged outwardly around said mounting plate and a frame protrusion that protrudes from at least one of said frame members away from said plate plane and that defines a clearance space therein, a free end of said extension arm extends into said clearance space, and said second vibration transducer arrangement is coupled to said free end of said extension arm and to said frame protrusion in said clearance space.

7. (original) The apparatus according to claim 3, wherein each one of said vibration transducer arrangements respectively comprises a vibration transducer connected to said outer frame, and an elastically flexibly bendable coupling rod

3896/WFF:ar

- 4 -

5 that is connected to said mounting plate and cooperates  
6 with said transducer to couple said transducer to said  
7 mounting plate.

1 8. (original) The apparatus according to claim 3, wherein at  
2 least one of said vibration transducer arrangements has a  
3 respective effective measuring axis, and is adjustably  
4 secured to at least one of said outer frame and said  
5 mounting plate so as to be slidably adjustable and  
6 selectively fixable in a direction parallel to said  
7 effective measuring axis.

1 9. (original) The apparatus according to claim 3, further  
2 comprising a third vibration transducer arrangement that is  
3 coupled to said outer frame and to said mounting plate, and  
4 that is so arranged and adapted to detect said pivotal  
5 vibration of said mounting plate relative to said outer  
6 frame about said pivot axis, wherein said second and third  
7 vibration transducer arrangements are respectively located  
8 spaced away from said pivot axis on two opposite sides of  
9 said pivot axis.

1 10. (original) The apparatus according to claim 2, wherein said  
2 pivot axis always lies in said plate plane.

1 11. (original) The apparatus according to claim 2, wherein said  
2 webs include a first pair of webs that extend along and  
3 parallel to said pivot axis respectively on opposite sides

3896/WFF:ar

- 5 -

of said mounting plate and that define said pivot axis, said webs further include a second pair of webs and a third pair of webs that respectively extend parallel to each other and parallel to said first pair of webs in said plate plane, and said second pair of webs and said third pair of webs are located respectively spaced equidistantly from said pivot axis on opposite sides of said pivot axis.

12. (original) The apparatus according to claim 11, wherein said webs of said second and third pairs of webs each respectively comprise a flexible sectional bar member having a square, rectangular, polygon or circular cross-sectional shape.

13. (original) The apparatus according to claim 11, wherein said webs of said second and third pairs of webs each respectively have at least one notch therein positioned so as to increase a flexibility of each respective said web in a direction perpendicular to said plate plane.

14. (original) The apparatus according to claim 2, wherein:

said webs include first, second and third pairs of webs;

said webs of each said pair are arranged axially aligned with each other respectively on opposite sides of said mounting plate;

said webs of said first pair of webs extend along and parallel to said pivot axis to define said pivot axis;

9           said webs of said first pair of webs are relatively  
10 more flexible with respect to torsion about said pivot axis  
11 so as to allow said pivotal vibration of said mounting  
12 plate and with respect to bending in said plate plane so as  
13 to allow said translational vibration of said mounting  
14 plate, and are relatively less flexible with respect to  
15 bending perpendicular to said plate plane so as to support  
16 and transmit said forces from said mounting plate to said  
17 outer frame;

18           said webs of said second and third pairs of webs are  
19 flexible with respect to bending in said plate plane so as  
20 to allow said translational vibration of said mounting  
21 plate and with respect to bending perpendicular to said  
22 plate plane so as to allow said pivotal vibration of said  
23 mounting plate; and

24           said webs of said first pair are stiffer than said  
25 webs of said second and third pairs with respect to bending  
26 perpendicular to said plate plane.

1    15. (original) The apparatus according to claim 2, wherein said  
2       webs include a first pair of webs that extend along and  
3       parallel to said pivot axis respectively on respective  
4       opposite sides of said mounting plate, and second and third  
5       pairs of webs that extend perpendicular to said pivot axis  
6       on respective opposite sides of said mounting plate.

1    16. (original) The apparatus according to claim 1, wherein said  
2       mounting plate has a rectangular plan shape including two

3 long sides and two short sides meeting each other at  
4 respective ends, and said webs include a first pair of webs  
5 arranged at a center of said long sides, and second and  
6 third pairs of webs arranged at said ends of said long  
7 sides.

1 17. (original) The apparatus according to claim 1, wherein at  
2 least one of said webs has at least one notch therein  
3 positioned so as to increase a flexibility of said web with  
4 respect to bending in said plate plane.

1 18. (original) The apparatus according to claim 1, wherein said  
2 rotation axis is oriented substantially vertically, and  
3 said plate plane is oriented substantially horizontally.

1 19. (original) The apparatus according to claim 1, wherein said  
2 rotation axis is oriented substantially horizontally, and  
3 said plate plane is oriented substantially vertically.

1 20. (original) The apparatus according to claim 1, wherein said  
2 webs include a first pair of webs that extend along an  
3 intersection of said plate plane and a plane containing  
4 said rotation axis.

1 21. (original) The apparatus according to claim 20, wherein  
2 said webs of said first pair each respectively have a  
3 cross-sectional shape that is flexurally stiff in a  
4 direction so as to resist bending due to said forces that

5 are oriented along said rotation axis and are not induced  
6 by the unbalance of the rotational body.

1 22. (original) The apparatus according to claim 21, wherein  
2 said cross-sectional shape is a rectangular cross-sectional  
3 shape having longer rectangle sides oriented perpendicular  
4 to said plate plane.

1 23. (original) The apparatus according to claim 1, wherein said  
2 mounting plate is connected and supported relative to said  
3 outer frame only by said webs, and expressly excluding all  
4 additional supports for said mounting plate and for the  
5 rotational body.

1 24. (original) The apparatus according to claim 1, wherein said  
2 mounting plate, said webs and said outer frame are  
3 integrally formed with one another so as to form thereof a  
4 single integral component.

1 25. (original) The apparatus according to claim 1, wherein each  
2 one of said vibration transducer arrangements respectively  
3 comprises a vibration transducer connected to said outer  
4 frame, and an elastically flexibly bendable coupling rod  
5 that is connected to said mounting plate and cooperates  
6 with said transducer to couple said transducer to said  
7 mounting plate.

3896/WFF:ar

- 9 -

1     **26.** (currently amended) A method of determining an unbalance of  
2     a rotational body, comprising the following steps:

- 3     a) mounting said rotational body on a mounting fixture of  
4     a dynamometer element;  
5     b) rotating said rotational body mounted on said fixture  
6     about a rotational axis;  
7     c) transferring all forces and moments originating from  
8     said rotational body into and through said dynamometer  
9     element, thereby causing at least a portion of said  
10    dynamometer element to undergo at least one of  
11    translational vibration in a plane of said dynamometer  
12    element and pivotal vibration about a pivot axis; and  
13    d) separately detecting a first one of said pivotal  
14    vibration and said translational vibration separately  
15    from a second other one of said vibrations using only  
16    a first sensor that is sensitive to only said first  
17    one of said vibrations without being sensitive to said  
18    second other one of said vibrations.

1     **27.** (previously presented) An apparatus for determining an  
2     unbalance of a rotational body when said rotational body is  
3     mounted on said apparatus so as to be rotatable about a  
4     rotation axis, said apparatus comprising:

5         a mounting plate extending along and defining a plate  
6     plane;

7         a mounting fixture that is arranged on said mounting  
8     plate, and that is adapted to receive the rotational body  
9     mounted thereon so as to allow the rotational body to

10 rotate about said rotation axis, wherein said rotation axis  
11 is oriented perpendicular to said plate plane;

12 an outer frame arranged at least partially outwardly  
13 around said mounting plate;

14 a plurality of webs respectively connecting said  
15 mounting plate to said outer frame, wherein said webs are  
16 so configured and arranged so as to support said mounting  
17 plate relative to said outer frame, to transmit from said  
18 mounting plate to said outer frame forces that are oriented  
19 along said rotation axis and that are not induced by the  
20 unbalance of the rotational body, to allow said mounting  
21 plate to undergo translational vibration relative to said  
22 outer frame in said plate plane, wherein said translational  
23 vibration is induced in said mounting plate by the  
24 unbalance of the rotational body, to define a pivot axis  
25 perpendicular to said rotation axis, and to allow said  
26 mounting plate to undergo pivotal vibration about said  
27 pivot axis; and

28 a first vibration transducer arrangement that is  
29 coupled to said outer frame and to said mounting plate, and  
30 that is so arranged and adapted to detect said  
31 translational vibration of said mounting plate relative to  
32 said outer frame in said plate plane;

33 wherein said webs include a first pair of webs that  
34 extend along and parallel to said pivot axis respectively  
35 on opposite sides of said mounting plate and that define  
36 said pivot axis, said webs further include a second pair of  
37 webs and a third pair of webs that respectively extend

38 parallel to each other and parallel to said first pair of  
39 webs in said plate plane, and said second pair of webs and  
40 said third pair of webs are located respectively spaced  
41 equidistantly from said pivot axis on opposite sides of  
42 said pivot axis.

1 28. (previously presented) An apparatus for determining an  
2 unbalance of a rotational body when said rotational body is  
3 mounted on said apparatus so as to be rotatable about a  
4 rotation axis, said apparatus comprising:

5 a mounting plate extending along and defining a plate  
6 plane;

7 a mounting fixture that is arranged on said mounting  
8 plate, and that is adapted to receive the rotational body  
9 mounted thereon so as to allow the rotational body to  
10 rotate about said rotation axis, wherein said rotation axis  
11 is oriented perpendicular to said plate plane;

12 an outer frame arranged at least partially outwardly  
13 around said mounting plate;

14 a plurality of webs respectively connecting said  
15 mounting plate to said outer frame, wherein said webs  
16 entirely support said mounting plate relative to said outer  
17 frame, said webs include a first pair of webs that extend  
18 axially aligned with one another along a pivot axis  
19 perpendicular to said rotation axis on opposite sides of  
20 said mounting plate and further webs offset away from said  
21 pivot axis, said webs of said first pair are torsionally  
22 flexible about said pivot axis to allow said mounting plate

23 to undergo pivotal vibration about said pivot axis and are  
24 flexurally stiff with respect to bending perpendicular to  
25 said plate plane, and said further webs are flexible with  
26 respect to bending perpendicular to said plate plane so as  
27 to allow said pivotal vibration of said mounting plate and  
28 with respect to bending in said plate plane so as to allow  
29 said mounting plate to undergo translational vibration in  
30 said plate plane;

31 a first vibration transducer arrangement that is  
32 coupled to said outer frame and to said mounting plate, and  
33 that is so arranged and adapted to detect said  
34 translational vibration of said mounting plate relative to  
35 said outer frame in said plate plane; and

36 a second vibration transducer arrangement that is  
37 coupled to said outer frame and to said mounting plate, and  
38 that is so arranged and adapted to detect said pivotal  
39 vibration of said mounting plate relative to said outer  
40 frame about said pivot axis.

1 29. (previously presented) The apparatus according to claim 28,  
2 wherein all of said further webs extend parallel relative  
3 to said webs of said first pair and relative to said pivot  
4 axis.

1 30. (previously presented) The apparatus according to claim 28,  
2 wherein all of said further webs extend respectively  
3 perpendicularly relative to said webs of said first pair  
4 and relative to said pivot axis.

3896/WFF:ar

- 13 -

1 31. (previously presented) The apparatus according to claim 28,  
2 wherein said further webs are arranged symmetrically on  
3 opposite sides of said pivot axis.

1 32. (previously presented) The apparatus according to claim 1,  
2 wherein said apparatus includes only a single one of said  
3 mounting plate, and said plural pairs of webs on said plate  
4 plane provide the only and entire support of said mounting  
5 plate.

1 33. (previously presented) The apparatus according to claim 1,  
2 wherein all of said pairs of webs are parallel to each  
3 other on said plate plane.

1 34. (previously presented) The apparatus according to claim 1,  
2 wherein said pairs of webs include one pair of said webs  
3 that is oriented perpendicular to another pair of said webs  
4 on said plate plane.

1 35. (previously presented) The apparatus according to claim 1,  
2 wherein said first vibration transducer arrangement has a  
3 first effective measuring axis that lies in the same plane  
4 as all of said plural pairs of webs.

1     **36.** (previously presented) The apparatus according to claim 3,  
2     wherein said second vibration transducer arrangement has a  
3     second effective measuring axis that is oriented  
4     substantially parallel to said rotation axis and  
5     substantially perpendicular to said plate plane.

1     **37.** (previously presented) The apparatus according to claim 3,  
2     wherein said first and second vibration transducer  
3     arrangements are both coupled directly to said outer frame  
4     and directly to said mounting plate.

1     **38.** (previously presented) The apparatus according to claim 3,  
2     wherein said first and second vibration transducer  
3     arrangements respectively have first and second effective  
4     measuring axes that are oriented perpendicular relative to  
5     each other.

1     **39.** (previously presented) The apparatus according to claim 3,  
2     wherein said first vibration transducer arrangement is  
3     arranged and oriented to detect only said translational  
4     vibration without being sensitive to said pivotal  
5     vibration, and said second vibration transducer arrangement  
6     is arranged and oriented to detect only said pivotal  
7     vibration without being sensitive to said translational  
8     vibration.

1     **40.** (currently amended) The method according to claim 26,  
2     further comprising, simultaneously during said step d),  
3     separately detecting said second other one of said  
4     vibrations separately from said first one of said  
5     vibrations using only a second sensor that is sensitive to  
6     only said second other one of said vibrations without being  
7     sensitive to said first one of said vibrations.

1     **41.** (previously presented) An apparatus for determining an  
2     unbalance of a rotational body when said rotational body is  
3     mounted on said apparatus so as to be rotatable about a  
4     rotation axis, said apparatus comprising:

5         a mounting plate extending along and defining a plate  
6     plane;

7         a mounting fixture that is arranged on said mounting  
8     plate, and that is adapted to receive the rotational body  
9     mounted thereon so as to allow the rotational body to  
10    rotate about said rotation axis, wherein said rotation axis  
11    is oriented perpendicular to said plate plane;

12        an outer frame arranged at least partially outwardly  
13    around said mounting plate;

14        a plurality of webs respectively connecting said  
15    mounting plate to said outer frame in an arrangement of  
16    said webs that is symmetrical relative to said rotation  
17    axis, wherein said webs are so configured and arranged so  
18    as to support said mounting plate relative to said outer  
19    frame, to transmit from said mounting plate to said outer  
20    frame all axially directed forces that are oriented along

21 said rotation axis and that are not induced by the  
22 unbalance of the rotational body, and to allow said  
23 mounting plate to undergo translational vibration relative  
24 to said outer frame in said plate plane, wherein said  
25 translational vibration is induced in said mounting plate  
26 by the unbalance of the rotational body; and

27 a first vibration transducer arrangement that is  
28 coupled to said outer frame and to said mounting plate, and  
29 that is so arranged and adapted to detect said  
30 translational vibration of said mounting plate relative to  
31 said outer frame in said plate plane;

32 wherein said webs are further so configured and  
33 arranged so as to define a pivot axis perpendicular to said  
34 rotation axis, and so as to allow said mounting plate to  
35 undergo pivotal vibration relative to said outer frame  
36 about said pivot axis, wherein said pivotal vibration is  
37 induced in said mounting plate by the unbalance of the  
38 rotational body;

39 further comprising a second vibration transducer  
40 arrangement that is coupled to said outer frame and to said  
41 mounting plate, and that is so arranged and adapted to  
42 detect said pivotal vibration of said mounting plate  
43 relative to said outer frame about said pivot axis; and

44 wherein said mounting plate comprises a plate body on  
45 which said mounting fixture is arranged and an extension  
46 arm protruding outwardly from said plate body, said outer  
47 frame comprises a plurality of frame members arranged  
48 outwardly around said mounting plate and a frame protrusion

49 that protrudes from at least one of said frame members away  
50 from said plate plane and that defines a clearance space  
51 therein, a free end of said extension arm extends into said  
52 clearance space, and said second vibration transducer  
53 arrangement is coupled to said free end of said extension  
54 arm and to said frame protrusion in said clearance space.

**[RESPONSE CONTINUES ON NEXT PAGE]**

3896/WFF:ar

- 18 -